


HD29H

HDR compatible Full HD 1080p gaming and entertainment projector









- Lights on viewing 3400 lumens
- 4K UHD HDR compatible
- Lightning fast gaming projector Supports 1080p 120Hz with 8.4ms response time
- Easy connectivity 2x HDMI, MHL, USB Power and 10W speaker

Convenient and easy to setup, the bright and versatile HD29H boasts HDR compatibility as well as delivering high contrast and accurate true to life colour reproduction. This compact projector is ideal for HDR gaming with support for 1080p 120Hz which provides a lightning fast response time of 8.4ms. You can even use it for watching live sport , TV shows and movies.



Specifications

Weight and dimensions

Dimensions (W x D x H)

Net weight

mm

Opcomodions	
Display/image	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness	3,400 lumens
Contrast ratio	50,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Keystone correction -	+/-40°
vertical	
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	80%
Screen size	0.71m ~ 7.65m (28" ~ 301") (diagonal)
Lamp info	
Light source type	Lamp
Lamp watts	203
Lamp life (hours)	6000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	4 47.4 - 4 00.4
Throw ratio	1.47:1 - 1.62:1
Projection distance (m) Zoom	1m - 9.8m 1.1
Zoom type	Manual
Focal length (mm)	15.59 ~ 17.14
Native offset	116%
Connectivity	11070
Connections	Inputs 1 x HDMI 2.0, 1 x HDMI
	Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A
	Control 1 x 3D sync
	- Control 1 X OB Oyno
General	0540
Noise level (typical) PC compatibility	25dB
PC compatibility	UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,
	4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,
	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz),
3D compatibility	4K UHD (24/30/50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:
3D compatibility	1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
cos, aspira, anguages	Finnish, French, German, Greek, Hungarian, Indonesian,
	Italian, Japanese, Norwegian, Polish, Portuguese, Romanian,
	Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Backlit home remote
Speaker count	1
Watts per speaker	10W
In the box	AC power cord, remote control, Battery, basic user manual
Input lag	8.40ms
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption	0.5W
(standby)	
Power consumption (min)	205W
Power consumption (max)	295W
Waight and dimensions	

2.87kg

316 x 244 x 108

