

PROFESSIONAL LOUDSPEAKERS
RF Series Installation Loudspeakers

Rigid and flexible loudspeakers for installation


RF 55

The RF 55 is a powerful 250 W column loudspeaker designed for high-quality audio in installed systems. Its configuration of 2x5" + 2x0.75" drivers provides excellent sound reproduction suitable for various music and speech applications.

With a dispersion of 120° horizontal and 20° vertical is good for controlled directivity in acoustic sensitive environments.

It can be mounted either as single unit or in multiples using the RF B55 mounting kit for flying.

The cabinet is constructed from durable paint-coated birch plywood, and it features convenient input and link connectors, including both phoenix and speakON options.



Technical Specifications	RF 55
Type	Column loudspeaker
Impedance	8 Ω
Rated Power	250 W RMS, 500 W peak
Sensitivity	94 dB, 1 W @ 1 m
Max SPL	122 dB
Frequency response	92 Hz - 20 kHz
Drivers	2 x 5" low frequency driver, 2 x 0.75" high frequency driver
Dispersion	120° (H) x 20° (V)
Connectors	SpeakON and Phoenix connectors for input and link
Dimensions	165 mm x 216 mm x 541 mm
Weight	9.6 kg
Material	Cabinet: plywood with texture coatig Grill: powder-coated metal
Mounting options	U-bracket (included), AMC RF UB universal angle mounting bracket (optional) Omnimount bracket & flying frame (optional)
Color	Black (RAL 9017)



U bracket included



Compatible with RF UB
universal mounting bracket

