

Highlights:

- · Setup any command behind any button in seconds
- No programming required
- Compatible with most TCP-IP supported AV equipment
- 4 adjustable buttons and push rotary with RGB LED ring indicator
- Transparent window for name tag (4x)

Product information:

The NCP105 is a universal network wall panel controller, with 4 programmable capacitive touch buttons and a programmable rotary encoder. Each button is provided with an RGB indicator LED, while the RGB LED ring gives the user feedback on the selected settings or audio level.

The IP-based communication makes it future-proof while also being backward compatible with many existing products.

Besides the elegant design, the front panel of NCP105 is finished with high-quality fingerprint-resistant glass and a name tag window for each button that allows a custom name tag to be added behind the panel, offering a neat finish while having a clear overview of the configured functions.

The configuration of the button functions and the rotary dial is entirely flexible, with full compatibility of all AUDAC Touch functionalities.

The NCP105's design allows it to be used in many applications and with many different AUDAC or third-party AV equipment. From simultaneous multi-device support such as processors, amplifiers, sources to loudspeakers, the choice is yours.

The wall panels are compatible with standard EU-style in-wall boxes, making the wall panel the ideal solution for solid and hollow walls. Black and white color options are available to blend into any architectural design.



Additional Inputs:

→ TCP-IP

System specifications:

Control			ogrammable touch buttons (transparent window ne tag)
		Pros	grammable rotary encoder
Indicators		RGE	B LED's (each button)
		360	° RGB LED light bar (16 LED)
Configurable settings		Fully	y configurable button & rotary functions - Routing
		Fully dow	y configurable button & rotary functions - Volume up / /n
		Fully	y configurable button & rotary functions - Mute
		Fully	y configurable button & rotary functions - Toggle relay
Configuration		Aud	ac Touch™
Power	Supply	PoE	powered (IEEE 802.3at)
Connectors		RJ45	5 (network + PoE)
Product Features:		1,	
Dimensions			80 x 80 mm (W x H) (Remote wall panel)
Colours			Black (RAL9005) (DWP105/B)
			White (RAL9003) (DWP105/W)
Front finish			Elegant ABS front panel with glass
Accessories	Optional	Surface mount Installation boxes	WB200 - Surface mount wall box for WP & DWP series
		Flush mount Installation boy	xes Flush mount box for 45 x 45 mm wall panel - Solid wall - WB45S/FS
			Flush mount box for 45 x 45 mm wall panel - Hollow wall - WB45S/FG
Construction			ABS
Installation standard			Compatible with EU installation materials
хи н			

Variants:

• NCP105/B - Black version

• NCP105/W - White version

