

Features

- Innovative & unique design
- High performance 8" woofer
- 200 Watt program power
- 108 dB of Max SPL
- Countless mounting possibilities
- High grade aluminium construction
- Compact & elegant design
- Wall mounting bracket included

Applications

- Bars & music cafés
- Night clubs & Discotheques
- Live musician performances
- Concert halls & ballrooms
- Mobile installations
- **.** . . .



The NOBA8 is a compact 8" bass cabinet which is characterized by an innovative & unique design. With its curved shape, made of 4 mm thick aircraft graded aluminum and its extremely powerful 8" woofer of 200 Watts, the NOBA8 is able to deliver an unheard low frequency response for its small woofer size.

The perfect acoustic experience is guaranteed when the entire audio frequency spectrum is equally distributed. The slick look of the NOBA8 allows it to be placed against a wall, on the ceiling or even underneath furniture, yet due to the unique composition of its parts, NOBA8 ensures a much better spreading of sound waves than other similar cabinets.

It is loaded with a 8" high-performance woofer constructed with a Max power handling of 200 Watt, with an RMS rating of 100 Watt. The strength of this loudspeaker originates from a 2.4" voice coil which is allowed to extra long excursions, combined with a large magnet size. Displacements are precisely controlled by the low-loss suspension resulting in a superior linear behaviour.

The input connection is made using a terminal block connector located at the inner side of the supporting structure, allowing close placement to any wall or corner.

An included wall mounting bracket offers convenient mounting possibilities to any wall, while fixation to ceilings is possible through optionally available accessories

▶Specifications

•		
SYSTEM SPECIFICATIONS		
Speaker type	8" Bass reflex cabinet	
Max. power subwoofer	200 Watt	
RMS power subwoofer	100 Watt	
Impedance	8 Ohm	
Sensitivity subwoofer (1W / 1m)	83 dB	
Sound pressure subwoofer (max W / 1m)	108 dB	
Frequency response (±3 dB)	90 Hz - 350 Hz	
Frequency range (-10 dB)	45 Hz - 350 Hz	
PRODUCT FEATURES		
Dimensions (Width x Height x Depth)	558 x 383 x 149 mm	
Weight net	8.75 Kg	
Driver	8" ferrite with 2.4" voice coil	
Connection	2-pin Terminal block connector (5.08 mm)	
Construction	Aluminium with plastic side covers	
Grill type	Plastic side grill	
Mounting & handling	Included wall mounting bracket	
Available colours	Black (RAL9004)	NOBA8/B
	White (RAL9003)	NOBA8/W
SHIPPING & ORDERING		
Packaging	Cardboard box	
Shipping weight & volume	11.5 Kg - 0.06 Cbm	
Accessories included	Wall mount bracket	
Optional accessories	MBK410C Ceiling mount bracket	

*AUDAC reserves the right to change specifications without notice: this is part of our policy to continuously improve our products.

► Architects' and Engineers' Specifications

► Technical drawing



