

VEXO112 12" high performance 2-way loudspeaker

Highlights:

- · Powerful sound experience
- · High sound pressure levels with tight driver response
- · Modern & elegant design
- · Impact resistant, ball impact proof
- DuraCoat™ texture paintwork
- Horizontal and vertical mounting
- Inclined Speakon connectors
- · 70V/100V transformer option available

Product information:

The VEXO1xx series are compact high performance 2-way loudspeakers and come in 4 different (active or passive) models. The low-frequency transducer, which is made out of high-quality materials, is combined with a 1.4 (VEXO108) or 1.7" (VEXO110, VEXO112 & Description of the compact of the co

Thanks to the unique driver composition, the VEXO112 delivers a clear and natural sound with an RMS power of 400 Watts and a maximum power of 1600 Watt. The frequency response (±3dB) starts from 58Hz up to 20 kHz and the sensitivity (1W/1m) reaches 99 dB while a maximum continuous sound pressure level from 125 dB can be achieved.

When not in use, the active versions of the VEXO series devices automatically go into an energy-saving standby mode. This means that active versions can also be used in fixed installations, as there is no need to physically shut them down after each use.

Using an optional 70V/100V line transformer enables the VEXO series to be used in 70V or 100V systems. By removing the backplate and replacing it with a 70V/100V backplate on which the module is integrated, the high-performance loudspeaker is able to apply in a 70V/100V system.

The construction of the cabinets is made of 15 mm plywood with a polyurethane coating, making them resistant to any impact. The front side of the cabinet is finished with a powder-coated steel grill with acoustical foam. A recessed carry handle on the rear side makes carrying easy. Positioning and suspension of the speaker are easily achieved by using the standard 35 mm pole adapter on the bottom and the M10 rigging points. Two speaker connectors provide reliable connections with easy link-through to cabinets.

The optional Clever U bracket allows mounting the high power 2-way cabinet both horizontally and vertically. An inclination of -90° to +35° ensures an optimal positioning. The optional MBK bracket even allows mounting the VEXO series to the ceiling which gives the opportunity to install the loudspeaker cleanly in any environment.





Impedance:

 Ω 80hm

Applications:

- Bars & Restaurants
- Education
- · Clubs
- Sporting facilities
- · Concert venues
- Events

System specifications:

| Speaker type | | 2-way |
|----------------------------|-------------------|---|
| Peak power handling | | 1600 W |
| Program power handling | | 800 W |
| RMS/AES power handling | | 400 W |
| Impedance | | 8 Ω |
| Sensitivity (1W/1m) | | 99 dB |
| Sound Pressure (Max. W/1m) | | 125 dB |
| Frequency | Response (± 3 dB) | 58 Hz - 20 kHz |
| Crossover | Туре | Passive built-in |
| Dispersion | Horizontal | 90° |
| | Vertical | 70° |
| Drivers | HF | Compression driver with 1.7" VC and 1" throat |
| | LF | 12" (2.5" VC) |
| Connectors | | 2 x Speakon compatible (Linkthrough) |

Product Features:

| Dimensions | | 369 x 610 x 390 mm (W x H x D) |
|---------------------|-------------------|--|
| Weight | | 22.4 kg |
| Construction | | 15 mm high-quality plywood |
| Finish | Cabinet finishing | Polyurethane coating |
| Front finish | | Powder coated steel grill with acoustical foam |
| Mounting & handling | Rigging points | 10 x M10 |
| | Stand fitting | 35 mm pole adapter on bottom |
| | Carry handles | On top |
| Accessories | Optional | 70V/100V transformer module |
| | | MBK112V Mounting bracket |
| Powerdrive mount | | Powerdrive type 100 (127 x 70 mm) |
| Colours | | Black & White |

Variants:

- VEXO112/B Black version
- VEXO112/W White version