

AVer MT300 Matrix Tracking Box





60 FPS



Up to 4K Output Resolution



HDMI In/Out



USB In/Out



PoE+



RS-422 Control



Intuitive Web UI



Supports NDI® HX3 Cameras Inputs



Built-in PTZ Link Premium



5 Years Warranty

Compact. Just Right.

The MT300's sleek and modern appearance is complemented by its compact design, making transportation and storage effortless. Additionally, its ingeniously engineered compact design allows for flexible installation options.



Device Management. Streamlined.

Enhance your streaming performance by viewing up to 4 live videos. With MT300's wide range of video inputs and outputs, you are free from the hassle of constantly plugging and unplugging devices.



Seamless Deployment. Versatile Settings.

The MT300 has been designed to suit any use case with its all-in-one camera control and video switching capabilities. Additionally, its PoE+ function allows you to get started shooting in no time without any additional power supply.



Existing Devices. Integrated.

The MT300 offers the flexibility to either bring your own device (BYOD) or integrate it with your existing devices, while leveraging its multimedia capabilities to take your presentation experience to the next level.



Web UI. Remote Management.

The simple web-based interface enables convenient remote access and management of cameras. Additionally, users can effortlessly create personalized profiles including display layouts to access their preferred settings promptly and efficiently.



PTZ Link Premium. Embedded.

It takes one step to convert AVer's PTZ camera into a voice-tracking camera with PTZ Link Premium. Built-in PTZ Link Premium functionality, you can create more device groups and mic channels, and automatic video switch combining with human detection auto tracking, making it ideal for presentation needs in hybrid environments.



Product Specifications

Power requirement	AC 100 - 240V to DC 12V/1.5A	LED indicator: STATUS	Orange: power on Green: operating Green (flashing): firmware upgrading
Power consumption	18W		
Dimensions (W x D x H)	15.0 x 21.0 x 4.3 cm		
Net weight	0.9 (± 0.1) kg	LED indicator: USB	Green: connected and standby
Storage conditions	Temperature: -20°C to +6 0°C Humidity: 20% to 95%	ELD marcator. COD	Green (flashing): UVC/UAC streaming
		LED indicator: LAN	Green: connected
Inputs	HDMI x 3 USB 2.0 Type-A x 3 RS-422 x 1 RJ-45 x 1 PoF+ x 1	Resolution	Inputs: up to 1080p 60 fps Outputs: up to 4K 60 fps
		Operating conditions	Temperature: 0°C to +50°C Humidity: 20% to 80%
		Outputs	HDMI x 2 USB 3.0 Type-B x 2
Communication protocol	RS-422		
Buttons	Power, Reset	PoE+	Yes, 42.5V to 57V 0.6A
Security	Kensington lock	Certification	CE, FCC, BSMI, NCC
Mounting bracket	Yes	Warranty	5 years

Package Contents

MT300, Power Adapter, Power Cable, Cable Fixing Plate (x2), Cable Tie (x13), 3.0 x 5 mm Flat Head Screw (x5), 3.0 x 5 mm Truss Head Screw (x4), M3 x 10 mm Screw (x4), Rack Mount Bracket (x2), USB 3.0 Cable (x2), RS-422 Cable, Quick Start Guide, Warranty Card*

Optional Accessories

Server Rack Mount, 3.0 x 5 mm Flat Head Screw (x3), 3.0 x 5 mm Truss Head Screw (x2)

Product Appearance

Front Rear







©2023 AVer Information Inc. All rights reserved. All brand names and logos are trademarks of their respective companies.



Distributor/Dealer

^{*} For Japan only.

** Specifications may vary depending on location and are subject to change without notice.