

**AVer**



AVer CAM130

## **Brighter and Better Meetings**

4K Camera with Intelligent Lighting for Small Rooms and WFH

# Product Specifications

## Camera

- 4K optical lens, 120° FOV, up to 4X zoom via ePTZ
- Sony 4K sensor: ultra-crystal-clear image in any lighting
- Frame rates: (16:9) 4K, 1920 x 1080, 1600 x 900, 1280 x 720, 960 x 540, 848 x 480, 800 x 448, 640 x 360, at 60, 30, 15fps; (4:3) 1280 x 960, 800 x 600, 640 x 480 at 60, 30, 15fps
- Intelligent fill light: automatically adjusts lighting levels to make you look energetic in a dim environment\*
- SmartFrame: automatically adjusts FOV to track and fit all participants onscreen
- Mirror, flip, AE, white balance: auto/manual override via PTZApp2
- Backlight compensation and 3D noise-reduction technology for optimizing light balance in different conditions
- Minimum focus distance: 60 cm
- People-counting API: enterprises and third-party software providers can obtain people-counting data for better understanding of meeting-space usage
- 10 camera presets (through remote control and IP web page)
- Standard tripod screw holes

\*For best lighting results, sit within 1 meter away from the camera

## Microphone

- 2 unidirectional microphones
- Frequency response: 100–12K Hz
- Sensitivity: -37 dB

## Connectivity

- USB type-C 3.1 connector, backward compatible with USB 2.0
- DC jack for power adapter (for USB 2.0 connection while using fill-light function)

## Video Format

- YUV, YUY2, MJPEG

## USB

- 3.1 Gen 1, backward compatible with USB 2.0
- UVC 1.1 (USB video), UAC 1.0 (USB audio)

## Control

- IR remote control
- UVC/UVA plug-and-play
- PTZApp 2

## Security and Mount

- Built-in TV clip
- Kensington slot
- 1/4" tripod mounting screw

## System Requirements

- Windows® 7/10
- MacOS X 10.7 or later
- Google Chromebook™ version 29.0.1547.70

## Hardware Specs

- 3.2 GHz Intel® Core™ i5-4460 processor
- 4 GB RAM or more
- USB 3.1 port, backward compatible with USB 2.0

## Power Supply

- AC 100V–240V, 50/60 Hz
- 5V/2A

## Free Applications for Meeting Collaboration (For Windows® and Mac® computers)

EZManager 2: Camera Central Management Software

- Remotely group FW/SW upgrades, control the camera, and manage settings

PTZApp 2: Camera Settings Software

- View live video, people-counting numbers, and meeting-interval information
- Enable Skype for Business far-end control
- Upgrade firmware automatically or manually
- Control the camera
- Set parameters and adjust the camera image
- Diagnose operating status

EZLive: Broadcasting Software

- Enjoy multi-camera real-time streaming, annotating, image capturing, and video recording

## Environmental Data

- Operation temperature: 0 to 40°C
- Operation humidity: 20% to 80%
- Storage temperature: -20 to 60°C
- Storage humidity: 20% to 80%

## Dimensions

- Package dimensions: 217(L)\*155(W)\*118(H) mm
- Package weight: 0.729 kg
- Camera: 160 (L) x 37 (H) x 60 (D) mm/ 0.282kg
- Remote control: 149.72 x 42.3 x 19.29 mm/50g (optional item)

## Package Contents

- CAM130 unit
- Power adapter (10 ft/3 m)
- USB 3.1 type-C to type-A cable (6 ft/1.8 m)
- QR code card
- Tripod screw

## Optional Accessories

- Remote control (also compatible with VB130)
- USB 2.0 type-C to type-A cable (15 ft/5 m)
- USB 3.1 Extension Cable (10 m/20 m/30 m)

## Warranty

- Camera: 3 years
- Accessories: 1 year

## Compatible Applications

Zoom, Microsoft® Teams, Skype for Business, Google Meet, RingCentral, BlueJeans, Intel® Unite™, Fuze, Adobe® Connect™, CyberLink U Meeting®, Cisco WebEx® GoToMeeting™, LiveOn, Microsoft® Lync™, TrueConf, V-Cube, Vidyo, vMix, WebRTC, Wirecast, XSplit

\*For 4K UHD support, please check system/hardware requirements with your software application provider.

\*\*Specifications may vary depending on countries and are subject to change without notice.

## Product Overview

**Front**



**Side**



**Back**

