USB Type C 7-in-1 Hub to HDMI[™] 4K60Hz /SD-TF Card slot 2x USB Type A / USB Type C PD / RJ45



Product Name

USB Type C 7-in-1 Hub to HDMI[™] 4K60Hz /SD-TF Card slot 2x USB Type A / USB Type C PD / RJ45

Product Series

Docking Station

Itemcode

CSV-1592

EAN code

8719214471477

UPC code

841615101658



The Club 3D CSV-1592 is a USB Type C 7-in-1 Hub to HDMI™ 4K60Hz /SD-TF Card slot / 2x USB Type A / USB Type C PD / RJ45, providing an ideal solution for extending the port of USB Type C or Thunderbolt™ 3 host (PC/Laptop/tablet/Mobile phone, etc.), especially for the host with a single USB Type C port. This hub adopts the latest DP 1.4 Alt mode technology available today, enabling to output HDMI™ video with max 4k/60Hz and at the meanwhile transfer USB 3.1 data with max 5Gbps. 2x USB Type A ports allow you to connect 2 USB devices simultaneously. SD/Micro SD allow to insert 2 card slots simultaneously for data transmission or for reading/writing information on the host. RJ45 ports allows the host to get access to Gigabit Ethernet. Besides, the USB Type C female supports PD 3.0 with max 100W PD Charging. It can work on all USB Type C and Thunderbolt™3 host that supports DP Alt mode(including DP1.2). Limited to USB Type C standards. When working on Thunderbolt™3 host, this product transmits DP signal.

In the box:

- CSV-1592 USB Type C 7-in-1 Hub to HDMI™ 4K60Hz /SD-TF Card slot / 2xUSB Type A / USB Type C PD / RJ45
- User Manual

Available Interfaces:

- ■Upstream:
- 1x USB Type C Male (Host connection)
- ■Downstream:
- 1x HDMI™ Female for connecting to Monitor
- 1x SD Card Slot
- 1x Micro SD Card Slot
- 2x USB type A, BC1.2 charging
- 1x USB Type-C female PD (Charging + Data)
- 1x RJ45

OS Support:

ΑII

Other info:

- Box size 32 x 6 x 3 cm
- Box size: 12.6 x 2.36 x 1.18 inch
- Device size: 13.6 x 3.4 x 1.4 cm
- Device size: 5.36 x 1.34 x 0.55 inch
- Device Weight: 69 gr / 2.43 oz
- LDPE Bag Weight: 5gr / 0.17 oz
- Box Weight: 36 gr / 1.3 oz
- Total Weight: 110 gr / 3.9 oz
- Meets ROHS, FCC, and CE EMI requirements



Features:

■ Upstream:

USB Type C Male (Connection to host)

Support DP 1.4 Alt mode, with bandwidth max 2 lanes 16.2Gbps (8.1Gbps per lane),downward compatible with DP1.2 Alt mode **Note:** To get max bandwidth, the host should support DP 1.4 Alt mode with DSC format.

■ Downstream:

Support HDMI $^{\rm M}$ max 4K/60Hz 4:4:4, 8bit with 18Gbps Bandwidth Support 6/8/10/12 bit color depth output

Support output pixel format RGB 4:4:4/YCbCr 4:4:4/YCbCr 4:2:2 Support HDCP 2.26HDCP1.4

Support HDR

Note: When connecting a DP 1.4 Alt mode supported host, the max resolution of HDMI is 4k/60Hz; When connecting a DP 1.2 Alt mode supported host, the max resolution of HDMI[™] is 4k/30Hz due to bandwidth limitation

■ 2x USB Type A 3.0

1- USB Type A port supports BC 1.2 with max. 7.5W(5V@1.5A) down-stream charging,

2- USB Type A share max. 8W (5V/1.6A) downstream charging. Max 5Gbps bandwidth per USB Type A port

■ SD/Micro SD

Support Secure Digital v3.0 UHS-I (Ultra High Speed)SDR12 (12.5Mbyte/s)/SDR25(25Mbyte/s)/SDR50(50Mbyte/s)/DDR50(50Mbyte/s)/SDR104(104Mbyte/s)

■ RJ45 (Gigabit Ethernet)

Support 10Mbps/100Mbps/1000Mbps

■ USB Type C Female (for PD Charging)

Support PD Charging 100W (20V/5A)

Support Fast Role Swap of PD 3.0, the connected device will not get disconnected while plugging in and out PD Adapter 8W is dedicated to the functioning of this product, the rest power (max 92W) will be passed to charge for the host

