

# innex CD Series

Redefining Digital Signage with Precision & Performance

## Vivid, Secure, and Versatile!



4K UHD



Brightness



Nonstop  
Productivity



178° Wide  
Viewing Angle



Software



Multi Size



Slim Bezel

## Unmatched for Any Space!

Captures attention in high-traffic areas with dynamic signage for promotions and information.



Corporate Offices & Meeting Rooms



Educational Institutions



Retail & Public Spaces



## Brilliance in Every Pixel!

The Innex CD Series delivers stunning 4K resolution, a 178° wide viewing angle, and versatile display options in sizes from 43" to 86". Perfect for meeting rooms, classrooms, and retail spaces, it offers 24/7 durability and both landscape and portrait modes. With cloud control, managing content and displays is simple, allowing seamless updates and synchronization from anywhere for enhanced efficiency.



## Excellent Visual Performance

### 4K Quality

The CD Series offers exceptional 4K quality, ensuring that every image is presented with stunning clarity and precision. With 60Hz refresh rate and a 178° viewing angle, the display provides the best visual quality and readability for all types of content.

### Portrait & Landscape Flexibility

The CD Series offers versatile portrait and landscape flexibility, easily switching between orientations to fit any content or environment.

### Durability for High-Demand Use

Designed for 24/7 operation, the CD Series is built to handle continuous, high-demand environments. Its durability ensures reliable performance around the clock, ideal for businesses needing dependable digital displays.

### Available in Multiple Sizes

The CD Series is designed to offer flexibility and versatility across a range of environments by providing multiple size options: 43", 55", 65", 75", and 86" displays.

## Easy & Secure Content Delivery



The Digital Signage Software makes content management easy and secure. With user-friendly configuration options, you can quickly set up a secure cloud server for sharing and controlling digital signage content. Authorized users can access displays remotely, ensuring that content updates are efficient and safe, no matter where you are.

# innexCD Series

## SPECS

Model		CD 43	CD 55	CD 65	CD 75	CD 86
Display	Display Dimension	43"	55"	65"	75"	86"
	Brightness	500cd/m2 (TYP)				
	Dynamic Contrast	5000:1				
	Anti-Glare	25% Haze				
	Back-Light	DLED				
	Resolution	3840x2160 (pixels, RGB)				
	Aspect Ratio	16:9				
	Response Time	8ms	8ms	6.5ms	8.5ms	8ms
	Viewing Angle	178°				
	Display Color	1.07B (10bit)				
	Panel Frequency	60 Hz				
	Life Time	30,000 Hrs (min.)				
I/O Ports	In	DC x1				
		RJ45 x1				
		USB OTG x1				
		USB 3.0 x1				
		HDMI x1				
		TF card x1				
	Out	Line x1				
	USB Type Wi-Fi Module	IEEE 802.11a/b/g/n/ac Dual Band 2.4/5GHz				
	Ethernet Network	10M/100M/1000M				
Power	Power Input	100V~240V AC				
	Rated Power Consumption	Maximum ≤ 150W	Maximum ≤ 180W	Maximum ≤ 220W	Maximum ≤ 280W	Maximum ≤ 380W
	Standby Power Consumption	≤ 0.5W				
	Speaker Output	10W x2				
Operating & Storage Environment	Operating Temperature	0 °C~ 45 °C				
	Storage Temperature	-10 °C~ 55 °C				
	Operation Humidity	20% ~ 80%RH				
	Storage Humidity	20% ~ 90%RH				
Embedded Operating System	Operating System	Android 11				
	RAM	DDR4 2GB				
	Internal Storage	32GB (EMMC)				
	CPU/GPU	Cortex-A55*4				
	UI Resolution	4K				
Physical Spec	Panel Dimension	960*550*65mm	1230*700*65mm	1450*825*65mm	1670*950*65mm	1920*1090*65mm
	Package Dimension	1090*680*160mm	1360*840*160mm	1545*930*165mm	1830*1145*195mm	2080*1295*195mm
	Net Weight	9.75kg	15.2kg	22kg	28.5kg	37.5kg
	Packed Weight	14.5kg	19.2kg	27kg	39kg	49.5kg
	VESA Mount Point	400*400mm	400*400mm	400*400mm	600*400mm	800*600mm
Compliance & Certification	Regulatory Certification	CE				
Accessories		1.5m HDMI Cable x1, 3m EU Power Cable x1, 3m UK Power Cable x1, Remote Control x1, Warranty Card x1, Safety Documents x1, Wi-Fi Dongle x1, Wall Bracket x1				