



ESP-230/WS

Order No.: 0190010

PRODUCTINFOS

Weatherproof PA speaker system,

in a white plastic cabinet with protective aluminium grille.

- 100 V line technique
- Hose-proof
- Switchable to 8 Ω operation
- 5 power taps, 8 Ω connection and 100 V power selector switch
- 2-way system
- Stainless steel mounting bracket

TECHNICAL SPECIFICATIONS

ESP-230/WS

| | |
|---------------------|---------|
| Active/passive | passive |
| Transmission method | 100 V |
| Total power rating | 100 W |

ESP-230/WS

| | |
|--------------------------------|----------------------------|
| | 30/20/10/5/2.5 W (100 V) |
| Power rating (RMS) | |
| | 50 W (8 Ω) |
| Impedance | 8 Ω |
| Frequency range | 80-20,000 Hz |
| System | 2-way |
| Number of speakers | 2 |
| Sensitivity | 92 dB/W/m |
| Housing material | plastic |
| Colour | white |
| Mounting device | mounting bracket |
| Protection class | IP65 |
| Admiss. ambient temp. | -20 °C to +50 °C |
| Dimensions | 157 x 260 x 170 mm |
| Width | 157 mm |
| Height | 260 mm |
| Depth | 170 mm |
| Weight | 1.8 kg |
| Inputs | spring-load. speaker term. |
| Packing dimensions (W x H x L) | 0.2 x 0.29 x 0.2 m |
| Gross weight | 2.276 kg |
| Net weight | 2 kg |