



## LSP-102

Order No.: 0251680

### PRODUCTINFOS

#### 2-channel 3-way line splitter,

(2 inputs/6 outputs), e.g. for connecting one mixer to several amplifiers.

- 1 balanced XLR input (600 Ω) for each channel
- 2 galvanically isolated, balanced XLR outputs (600 Ω) with ground lift switch for each channel
- 1 balanced XLR direct output for each channel
- Frequency range: 20-20,000 Hz
- Robust metal housing with very good shielding qualities, suitable for stage applications
- Dimensions: 160 x 55 x 105 mm
- Weight: 909 g

#### SOUNDCHECK 07/2007

on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:

“Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price.”

## tools4music 06/2009

on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102

“Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the 'ever accompanying' tool case.”

## TECHNICAL SPECIFICATIONS

### LSP-102

Description	splitter
Frequency range	20-20,000 Hz
Input impedance	600 Ω
Output impedance	600 Ω
Admiss. ambient temp.	0-40 °C
Dimensions	160 x 55 x 105 mm
Weight	909 g
Inputs	2 x XLR, bal.
Outputs	6 x XLR, bal.
Other features	ground lift switch