



PA-1480

Order No.: 0171110

PRODUCTINFOS

Mono PA power amplifier

- 1 x 480 W
- Switchable 400 Hz high-pass filter 6 dB/oct.
- Temperature-controlled fan, continuously adjustable
- LED indication for clip, protect, overtemperature and output level
- Feed-through output (link)
- Mains operation or 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-1480

Power rating	480 W
Power rating at 8 Ω	1 x 480 W
Power rating at 100 V	1 x 480 W
Output impedance	62 V/8 Ω, 70 V/10 Ω, 100 V/21 Ω
Channels	1
Inputs	1.2 V, bal.
Frequency range	35-20,000 Hz
S/N ratio	> 100 dBA
THD	< 1%
Mains voltage	~ 230 V

PA-1480

Mains frequency	50 Hz
Power consumption, operation	1,400 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 40 A
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	88 mm
Depth	374 mm
Rack spaces, RS	2
Weight	15.2 kg
Connections	XLR/screw contacts (inputs) screw contacts (speakers)
Packing dimensions (W x H x L)	0.58 x 0.18 x 0.48 m
Gross weight	17.24 kg
Net weight	15.22 kg