



482 mm





PA-1850D

Order No.: 0172960

PRODUCTINFOS

8-channel class D PA amplifier

- 8 x 50 W
- Class D concept with a high efficiency to cut energy costs
- Requires a lower rechargeable battery capacity for emergency power operation than 100 V analogue amplifiers
- Clearly reduced cooling requirements due to low heat dispersion
- Silent operation due to fanless cooling concept
- Mute function for each channel
- Level control for each channel
- LED indication for clip and protect for each channel pair
- Protected against short circuit
- Mains operation or 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-1850D

Power rating 400 W
Power rating at 4 Ω 8 x 50 W
Power rating at 100 V 8 x 50 W
Output impedance 4 Ω , 70/100 V

Channels



PA-1850D

Depth

Inputs $\begin{array}{c} 1 \text{ V/20 k}\Omega \text{ unbal.} \\ 550 \text{ mV/20 k}\Omega \text{ bal.} \end{array}$

Frequency range 10-20,000 Hz

S/N ratio > 65 dB THD < 0.5% Mains voltage ~ 230 V Mains frequency 50 Hz Power consumption, operation 600 VA Operating voltage (possible alternative) DC 24 V Power supply (possible alternative) DC 18 A 0-40 °C Admiss. ambient temp. Width 483 mm Height 90 mm

Rack spaces, RS 2

Weight 18 kg

8 x XLR input, bal.

398 mm

Connections 8 x RCA input,

screw contacts (speakers)

Packing dimensions (W x H x L) $0.47 \times 0.17 \times 0.58 \text{ m}$

Gross weight 20.45 kg
Net weight 18.17 kg