



## PA-2400RC

Order No.: 0236840

### PRODUCTINFOS

#### PA zone paging desktop microphone,

for connection to PA-1120, PA-1240, PA-2420Z, PA-6010Z or PA-6020Z.

- Selection buttons for speaker zones 1-20
- Start/stop function for 6 selectable announcements which are stored in the digital module PA-1120DMT, available at option
- LED indication for various functions
- Automatic chime via microphone announcement button
- Adjustable microphone sensitivity
- 24 V power supply via PA-2410Z, PA-2420Z
- RJ45 jacks for connection to additional PA-2400RC with slave/priority switch
- Up to 3 x PA-2400RC can be connected to PA-2410Z or PA-2420Z
- Supplied with 3 m connection cable (Cat. 5e)

### TECHNICAL SPECIFICATIONS

**PA-2400RC**

Description	PA desktop microphone
Transmission method	cable
Power supply	via PA-2410Z, PA-2420Z
Admiss. ambient temp.	0-40 °C
Dimensions	275 x 51 x 156 mm (console housing)
Weight	1.4 kg
Connection	RJ45 (input/link)
Packing dimensions (W x H x L)	0.2 x 0.27 x 0.32 m
Gross weight	1.9 kg
Net weight	1.56 kg