



PA-4120

Order No.: 0170810

PRODUCTINFOS

PA power amplifier

- 4 x 120 W
- Routing switches for parallel operation on 2 channels each
- Temperature-controlled fan
- Connection for external on/off switch
- LED indication for clip, protect, overtemperature and output level
- Mains operation or 24 V emergency power operation

TECHNICAL SPECIFICATIONS

PA-4120

Power rating	480 W
Power rating at 4 Ω	4 x 120 W
Power rating at 100 V	4 x 120 W
Output impedance	22 V/4 Ω , 50 V/21 Ω , 70 V/41 Ω , 100 V/83 Ω
Channels	4
Inputs	1.2 V, bal.

PA-4120

Frequency range	55-17,000 Hz
S/N ratio	> 90 dBA
THD	< 1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,400 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	DC 60 A
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	133 mm
Depth	370 mm
Rack spaces, RS	3
Weight	25 kg
Connections	4 x XLR (inputs), screw terminals (speakers)
Packing dimensions (W x H x L)	0.48 x 0.22 x 0.54 m
Gross weight	27.6 kg
Net weight	25.68 kg