



^{4Ω} □ Dante

PA-900DT

Order No.: 0176080

PRODUCTINFOS

Let's stream ...

The well-known and reliable amplifier systems PA-900 and AKB-160 now feature a 2-channel Dante® module which turns them into Dante® instreamers for versatile applications. They are able to receive one digital stereo signal or two mono signals via the RJ45 connections. These signals are converted into an analogue audio signal, amplified and then streamed. Thus, it is possible to integrate an analogue speaker system into a digital Dante® network.

Mono PA mixing amplifier with integrated Dante® module

- 1 x 120 W
- · Silent operation due to fanless cooling concept
- 3 balanced mic/line inputs
- Dante[®] input
- Mic 1 with priority circuit and automatic talkover
- Additional connection for desktop microphone via screw terminal
- 1 aux input
- Speaker outputs via screw terminal contacts
- · Line output
- Insert facility, e.g. for effect units, equalizers, feedback controllers
- · Input and output level controls
- 2-way tone control for the output
- 20 V phantom power for each microphone input, can be activated individually
- Mains operation or 24 V emergency power operation



• Removable mounting brackets

System requirements Dante®: Windows* 7/8.1/10 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd.

TECHNICAL SPECIFICATIONS

PA-900DT

| Peak output power | 160 W |
|----------------------------|-------|
| Power rating | 120 W |
| Power rating at 4 Ω | 120 W |
| Power rating at 100 V | 120 W |
| Channels | 5 |

3 mV (mic),

Inputs 200 mV (line),

140 mV (aux)

Frequency range 50-15,000 Hz Equalizer bass \pm 10 dB/100 Hz Equalizer treble \pm 10 dB/10 kHz

S/N ratio $> 80 \, dB$ THD < 0.5% Phantom power 20 V ~ 230 V Mains voltage Mains frequency 50 Hz Power consumption, operation 300 VA DC 24 V Operating voltage (possible alternative) Power supply (possible alternative) DC 9 A Admiss. ambient temp. 0-40 °C Width 482 mm 88 mm Height Depth 275 mm Rack spaces, RS 2 Weight 9.9 kg



PA-900DT

3 x XLR (mic/line),

1 x RCA L/R (aux),

Connections $1 \times RJ45$ (Dante[®]),

screw contacts (speakers)

Packing dimensions (W x H x L) 0.37 x 0.16 x 0.52 m

Gross weight 12.07 kg
Net weight 10.53 kg