



PA-948S

Order No.: 0177020

PRODUCTINFOS

Mono PA power amplifier

- 1 x 480 W
- Temperature-controlled fan, continuously adjustable
- Protected against overheating, overload and short circuit
- LED indication for clip, protect, overtemperature, output level and 100 V/70 V
- Feed-through output (link)
- Speaker outputs via screw terminal contacts

TECHNICAL SPECIFICATIONS

PA-948S

Power rating	480 W
Power rating at 100 V	1 x 480 W
Output impedance	70 V/10 Ω , 100 V/20 Ω
Channels	1
Inputs	710 mV/10 k Ω , balanced
Frequency range	80-16,000 Hz
S/N ratio	> 98 dBA
THD	< 1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	1,100 VA
Admiss. ambient temp.	0-40 °C

PA-948S

Width	483 mm
Height	44 mm
Depth	255 mm
Rack spaces, RS	1
Weight	4 kg
Connections	1 x combo 6.3 mm/XLR (input), 1 x XLR (link), screw contacts (speakers)
Packing dimensions (W x H x L)	0.36 x 0.14 x 0.54 m
Gross weight	5.23 kg
Net weight	4.28 kg