



PA-M4RC

Order No.: 0179310

PRODUCTINFOS

PA zone paging microphone,

for PA matrix mixing amplifier PA-M224 or PA-M412.

- 4 zone selector switch
- ALL-CALL button
- Plug-in electret gooseneck microphone (3-pole XLR jack)
- Phantom power for gooseneck microphone
- LED indication for signal status
- Power supply via PA-M224 or PA-M412
- Connection to PA-M224 or PA-M412 via RJ45 jack and Cat. 5e network cable (copper, supplied w/o cable), cable length up to 200 m

TECHNICAL SPECIFICATIONS

PA-M4RC

Description

PA zone paging microphone

Transmission method

cable

PA-M4RC

| | |
|--------------------------------|----------------------|
| System | electret |
| Power supply | via PA-M224, PA-M412 |
| Audio frequency range | 45-15,000 Hz |
| Sensitivity | 1 mV/Pa |
| Gooseneck length | 420 mm |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 140 x 65 x 205 mm |
| Weight | 860 g |
| Connection | RJ45 |
| Packing dimensions (W x H x L) | 0.1 x 0.21 x 0.35 m |
| Gross weight | 1.09 kg |
| Net weight | 0.86 kg |