



# STA-200D

Order No.: 0255070

## PRODUCTINFOS

### Stereo class D PA amplifier, 250 W

- 5 switchable line inputs
- Silent operation due to fanless cooling concept
- High power reserves due to generously dimensioned toroidal core transformer
- High-efficiency power amplifiers
- 3.5 mm stereo jack connection with switchable sensitivity on the front panel
- 4 x RCA input
- 2 x SPEAKER output
- 4 x terminal strip output
- 2 level controls
- Protected against short circuit, overvoltage and overtemperature
- LEDs for indicating power, overload (clip), protect and overheating
- Super slimline and robust design, 1 RS

## TECHNICAL SPECIFICATIONS

### STA-200D

Peak output power	300 W
Power rating	250 W
Power rating at 4 $\Omega$	2 x 125 W
Power rating at 8 $\Omega$	2 x 75 W
Channels	2
Inputs	1 V/23 k $\Omega$ (RCA), 90 mV-1 V (jack)

**STA-200D**

Frequency range	20-20,000 Hz
S/N ratio	> 100 dBA
Crosstalk attenuation	> 56 dB
THD	< 0.05%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	350 VA
Admiss. ambient temp.	0-40 °C
Width	483 mm
Height	44 mm
Depth	268 mm
Rack spaces, RS	1
Weight	5 kg
Connections	1 x 3.5 mm stereo jack 4 x RCA L/R 1 x SPEAKER L/R 1 x spring-load. speaker term. L/R
Packing dimensions (W x H x L)	0.34 x 0.1 x 0.46 m
Gross weight	5.9 kg
Net weight	5.15 kg