newline





Superior Image Quality



Seamless Wireless Casting



Access to the Cloud



Non-Touch Display



Impressive Embedded OS



Remote Management



Control by Remote



Compatible with all Devices

STREAMLINE YOUR SUCCESS

The NT Series is a non-touch display that brings your lessons to life in vivid Ultra-High Definition (4K) resolution. Focus on just the tools you need to get your students engaged in class without paying more for features you won't use.

Wirelessly cast to the screen from any mobile device, tablet, desktop, or laptop. Whether you use Windows, Mac, or Chrome, the NT Series lets you share your screen through a wireless connection or through the multiple I/O ports built into the panel. Access your files on your preferred Cloud storage system right on the display. The built-in file viewer lets you easily navigate through local files, Cloud storage, and files from connected USB thumb drives.

Rediscover the simplicity of real innovation with the new NT Series.

Newline NT Series includes the following software solutions



BROADCAST

NT Series

Model	NT65	NT85	NT98	
Display				
Screen Size	65"	85"	98"	
Display Area	56.2 x 31.6 in	73.7 x 41.5 in	85 x 47.8 in	
Backlight	LED	LED	LED	
Resolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	
Display Ratio	16:9	16:9	16:9	
Brightness	≥400 cd/m²	≥400 cd/m²	≥400 cd/m²	
isplay Colors	8 bit	8 bit	10 bit	
ynamic Contrast	4000:1	4000:1	4000:1	
laze	2%~5%	2%~5%	25%~28%	
iewing Angle	178°	178°	178°	
ifetime Hours	50,000 hours	50,000 hours	50,000 hours	
Continuous Run Time	24/7	24/7	24/7	
Speakers				
Position	Downward	Downward	Downward	
ated Impedence	6Ω	6Ω	6Ω	
requency Response	Fb-20KHz/-10dB	Fb-20KHz/-10dB	Fb-20KHz/-10dB	
Output S.P.L.	0dB~ -10dB	0dB~ -10dB	0dB~ -10dB	
Max Power Output	(2) 20W	(2) 20W	(2) 20W	
/licrophone	()			
nternal Microphone	6-mic array	6-mic array	6-mic array	
rickup Range	19.7 - 26.2 ft	19.7 - 26.2 ft	19.7 - 26.2 ft	
cho Cancellation	Yes	Yes	Yes	
loise Reduction	Yes	Yes	Yes	
leverb Removal	Yes	Yes	Yes	
ower	100	100	100	
Max Power Consumption	≤200W (Standby ≤0.5W)	≤450W (Standby ≤0.5W)	≤700W (Standby ≤0.5W)	
	AC100-240V Max 4.5A	AC100-240V Max 4.5A	AC100-240V Max 7.0A	
Vorking Voltage ransportation/Storage	AC100-240V Max 4.3A	AC 100-240 V Max 4.5A	AC 100-240V Max 7.0A	
	14°F 112°F / 20°V 00°V	14°F 112°F / 200/ 000/	14°F 113°F / 200/ 000/	
torage Temp/Humidity	14°F~113°F / 20% - 90%	14°F~113°F / 20% - 90%	14°F~113°F / 20% - 90%	
Vorking Temp/Humidity	32°F - 104°F / 20% - 80%	32°F - 104°F / 20% - 80%	32°F - 104°F / 20% - 80%	
Mounting Options	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	
ESA Mount	600x400mm	800x400 mm	800x600 mm	
utline Dimensions	59 x 34.9 x 3.3 in	77.4 x 43.4 x 3.4 in	87.1 x 50.9 x 3.7 in	
let Weight	62 lbs	113 lbs	190 lbs	
mbedded Operating System	A7010 A5010	47010 : 7712	A7010, A7010	
PU	A73*2+A53*2	A73*2+A53*2	A73*2+A53*2	
PU	G51*4	G51*4	G51*4	
AM	3 GB DDR4	3 GB DDR4	3 GB DDR4	
OM	16GB	16GB	16GB	
ndroid Version	8.0.0 8.0.0			
Multimedia Files Supported	Image: JPEG, BMP, PNG; Video: MI	PEG2, MPEG4, H264, HEVC (H.265); Audio:	WMA, MP3, M4A, (AAC)	
orts				
nput Ports	(4) HDMI 2.0; (4)USB 3.0; (1) USB	(4) HDMI 2.0; (4)USB 3.0; (1) USB (For touch passthrough); (1) LAN in; (1) RS232		
output Ports	(1) LAN out; (1) SPDIF out; (1) He	(1) LAN out; (1) SPDIF out; (1) Headphones out		
DPS Slot	YES 4K@60HZ			

