

SIMPLY SMARTER COLLABORATION

The $\it 4K\ TRUTOUCH\ X\ series$ features InGlass $^{\rm m}$ technology for superior writing experience and combines advanced technology with elegance.



COLLABORATION INTERACTIVE PRESENTATION

TRUTOUCH X series debuts with evolutionary innovation leading the way to a brand new user experience like you never expected.

COMMUNICATE BETTER, COLLABORATE EASIER

Featuring Montage UC sofeware for easy collaboration anytime, anywhere.






SUPERIOR WRITING EXPERIENCE

Advanced InGlass™ technology for responsive touch digital whiteboard with seamless writing experience.

CLEAR AND ROBUST IMAGE

X series makes use of the latest optical bonding technology which reduces reflections resulting in improved contrast and reduced parallax. With 4K UHD resolution, the X9 delivers clear and robust images that give you the best video conferencing experience.



POWERED BY



Communication connect anything



Quick access annotation & intuitive interface



Wireless Collaboration Connect with Any Device

Remote PC Control



Video / Voice Communication

All New Interface



Multi-OS






FEATURES

Optical Bonding makes the touch panel more sturdy and protects the display from dust and moisture. **All-in-one** system requires no additional equipment such as camera microphone nor speakers. **With OPS slot**, users can install any of favorite Windows applications without limit.



USER INTERFACE

Efficient meetings on the go with easily accessible



Scheduling function for meeting room schedules.



Enhance communication with discussion board/annotation.



FloatNSplit ablet keyboard



Business Calendar









Become an expert with an intuitive interface.



One click share by Email or USB flash.



Model	X6	Х8	X9
•		Display	
Backlight		LED	
Display Area	1428.48 x 803.52 mm	1650.24 x 928.26 mm	1897 x 1068 mm
Active Screen Size	65"	75"	86"
Display Ratio		16:9	
Resolution		3840 x 2160 Pixels	
Display Colors	8-bit	8-bit	10-bit
Brightness	≥320nit	≥320nit	370nit
Contrast		4000:1	
Response Time		8ms	
/iewing Angle		178°	
ife Time		30000Hrs(Min.)	
<u> </u>	Ş	Speaker	
Speaker position		Forward	
Rated Impedance	80		
requency Response	20-18K Hz		
Output S.P.L.	≤13W		
Max.Power Output		2 x15W	
	Mi	crophone	
Sensitivity	IVIII	-38dBV±3dB	
Frequency Response	-36UDV±3UB 65Hz - 12.5KHz		
Polar Patterns	Omni-directional		
THD +N (1kHz @ +4dBu)	<0.05%		
Pickup Range	8 meters		
Quantity	4 (1 Array)		
quantity		Camera	
S			\
Position	Top x1 & Bottom x1 (Only one can use in the same time)		
Sensor		2M Pixels	
_ens	86°		
/ideo Resolution	1920 x 1080@30fps (Max)		
Frame Rate	_	30fps/60fps	
		lectrical	
Power Consumption	Maximum ≤220W	Maximum ≤300W	Maximum ≤450W
·	Standby Mode ≤0.5W	Standby Mode ≤0.5W	Standby Mode ≤0.5W
Vorking Voltage		AC 100-240V, 50/60Hz	
		Touch	
Touch Surface	Optical Bonding Anti-Glare & Anti-Fingerprint Glass		
ransparency		88%	
Surface Hardness		7H	
Touch Technology	InGlass™		
Touch Points	20 Points Touch in Windows/ 3 Points Touch in Embedded System		
Writing Tools	Stylus or Finger		
Communication Interface	_	USB-A	
	Transpor	rtation/Storage	
Storage Temperature/Humidity	-10°C - 50°C/10% - 90%		
Marking Toponoroturo / Lumiditu	0°C - 40°C/10% - 90%		
	Wall-mounted / Floor Stand		
Mounting (optional)	150 (2:5)		
Working Temperature/Humidity Mounting (optional) Outline Dimension	1568x1045x88mm	1792x1170x102mm	2039x1315x101mm
Mounting (optional) Outline Dimension	45 kg	1792x1170x102mm 55 kg	2039x1315x101mm 71.6 kg
Mounting (optional) Outline Dimension	45 kg	1792x1170x102mm 55 kg Ports	71.6 kg
Mounting (optional) Dutline Dimension Net Weight	45 kg HDMI 1.4 (4K@30⊢	1792x1170x102mm 55 kg Ports Iz) x1, USB(Touch) x1, USB (Dynamic) x2	71.6 kg z, Microphone In x1
Mounting (optional) Outline Dimension Net Weight Front Interface Inputs AV Inputs	45 kg HDMI 1.4 (4K@30H HDMI (4K@60H	1792x1170x102mm 55 kg Ports Hz) x1, USB(Touch) x1, USB (Dynamic) x2 Hz x2, 4K@30Hz x1), DP (4K@60Hz) x1, USB	71.6 kg , Microphone In x1 USB (Touch) x4
Mounting (optional) Dutline Dimension Net Weight Front Interface Inputs	45 kg HDMI 1.4 (4K@30H HDMI (4K@60H HDM	1792x1170x102mm 55 kg Ports Hz) x1, USB(Touch) x1, USB (Dynamic) x2 Hz x2, 4K@30Hz x1), DP (4K@60Hz) x1, I MI Out (4K@60Hz) x1, Line Out x1, SPDIF	71.6 kg r, Microphone In x1 USB (Touch) x4
Mounting (optional) Dutline Dimension Net Weight Front Interface Inputs AV Inputs	45 kg HDMI 1.4 (4K@30H HDMI (4K@60H HDM	1792x1170x102mm 55 kg Ports Hz) x1, USB(Touch) x1, USB (Dynamic) x2 Hz x2, 4K@30Hz x1), DP (4K@60Hz) x1, USB	71.6 kg 2, Microphone In x1 USB (Touch) x4



Newline Interactive Inc. 101 East Park Blvd. Suite 807 Plano, TX 75074, USA TEL: +1 888 233 0868

Want to buy: info@newline-interactive.com Become our partner: partner@newline-interactive.com Europe office Ronda de Poniente, N'2, 1ª planta, Oficina 1B, 28760, Tres Cantos, Madrid, Spain TEL: +34 911169178 Want to buy: info_eu@newline-interactive.com

partner_eu@newline-interactive.com

Become our partner:

Asia Pacific Office 4F-3, No.76 Sec.2, Jiafeng S. Rd, Zhubei City, Hsinchu Country, 30272, Taiwan TEL: +886 35504768 Want to buy: info_ap@newline-interactive.com Become our partner: partner_ap@newline-interactive.com India office
Room No. 203, No. 37, TTK Road,
Alwarpet, Chennai,
Tamil Nadu, India, 600018
TEL: +91 4446945513
Want to buy:
info.in@newline-interactive.com
Become our partner:
partner.in@newline-interactive.com