

# AT-200

## Automated Audio Guide















Multi-function audio guide  
with different triggers!

AT-200 with more customization to  
your scenario.



### | Features

-  Lithium battery powered, 11+ battery hours per charge.
-  Full color OLED screen and illuminated keypad.
-  Built-in HAC speaker.
-  Twin Hi-Fi stereo earphone jacks.
-  32 languages, 9,900 tracks per each.
-  4 options for audio triggering **IR, RF, RFID** and **GPS** triggers.
-  Data collection for visitor flow, management and analysis.
-  Built-in anti-theft function.
-  Expandable 8 GB memory delivers 2,000+ minutes play time.
-  2<sup>nd</sup> layer audio track for assistive information.
-  5 minute speedy cloning track content with ATC-221U, 20 slots at the same time.



**okayo** Audio Master 3  
An easy compiling PC-based  
platform for audio management



auto triggering



anti-theft



OLED display



data collection

Spot 1

Spot 2



**ATC-210**  
10-slot charger



**ATC-210U**  
10-slot charger  
and uploader



**ATC-220**  
20-slot charger



**ATC-221U**  
20-slot uploader



**ATC-250**  
50-slot charger

## AUDIO PARAMETERS

Audio format	High quality audio compression
Frequency response	50 Hz ~ 18 kHz
Dynamic range	95 dB
Distortion	< 0.1 %
Speaker	Built-in 0.5 W @ 8 Ω
Earphone output	3.5 mm Jack x 2 (stereo)

## GENERAL PARAMETERS

OLED display	1.3 inch (Full Color 128 x 96)
Memory capacity	8 GB
Automatic triggering	IR, RF, RFID and GPS
Alarm	Anti-theft system
Number of language	Max. 32
Number of message	Max. 9900 x 32
Operating temperature	-10 °C ~ 50 °C
Battery	3.7 V, 1200 mAh Li-Polymer battery
Battery life	11 hours
Charging time	5 ~ 6 hours
Dimensions (D x W x H)	29.6 x 55.3 x 200 mm
Weight	180 g (with battery)

## UPLOADER SPECIFICATIONS

Software	OKAYO Audio Master 3 OKAYO Data Master
OS Support	Windows 7/10
Upload interface	USB 1.1 / USB 2.0
Upload speed	2.5 Mbytes / sec @ ATC-110U Uploader 20 pcs @ 5 Mbyte / sec @ ATC-221U Uploader