












# AT-500

## Interaction Audio Guide

Intuitive touch panel screen!

### | Features

-  Number input or menu select.
-  2.8 inch QVGA touch-screen display.
-  Support slides, pictures and text.
-  Twin Hi-Fi stereo earphone jacks.
-  32 languages, 9,999 tracks per each, with 8 GB memory.
-  Lithium battery powered, 12+ battery hours per charge.
-  Built-in HAC (Hearing aid compatible) speaker.
-  Auto triggering via IR.
-  Lip accurate "video sync."
-  Built-in anti-theft function and data collect.
-  Hassle free wireless charging.





touch panel



wireless  
charging



video sync



data collection

## | Charger



**ATC-528U**  
28-slot wireless charger and uploader

### **okayo** Audio Master 5

An easy compiling PC-based platform  
for audio management



### AUDIO PARAMETERS

Audio format	High quality audio compression
Bandwidth	20 Hz ~ 18 kHz
Dynamic range	90 dB
Distortion	< 0.1 %
Speaker	Built-in 1 W @ 8 Ω
Earphone output	3.5 mm Jack x 2 (stereo)

### GENERAL PARAMETERS

Touch-screen display	2.8 inch TFT-LCD (240*RGB*320)
Memory capacity	8 GB
Automatic triggering	IR
Alarm	Anti-theft system
Number of language	Max. 32
Number of message	Max. 9999 x 32
Operating temperature	-10 °C ~ 50 °C
Battery	3.7 V, 1700 mAh Li-Polymer battery
Battery life	12 hours
Charging time	6 ~ 7 hours
Dimensions (D x W x H)	23.2 x 61.5 x 135 mm
Weight	175 g (with battery)

### UPLOADER SPECIFICATIONS

Software	OKAYO Audio Master 5
Support OS	Windows 7 / 10
Upload interface	USB 1.1 / USB 2.0
Upload speed	5 Mbytes / sec