

HD35UST

1080p ultra short throw home entertainment projector



- Lights on viewing bright 3600 lumens
- Ultra short throw lens 100" image from less than half a metre away
- Enjoy live sports, TV shows and gaming in Full HD 1080p
- Easy to setup horizontal and vertical keystone and four corner adjustment

Experience a super-sized 100-inch image with this ultra short throw projector placed just 30cm away from a wall or screen. Perfect for live sports, TV shows, films and gaming with it's bright, razor sharp images with optimum colour performance even with the lights on.

An integrated speaker provides great sound and two HDMI inputs enables an easy setup. You can even turn it into a smart projector by connecting a HDMI dongle like the Google ChromecastTM, Amazon Fire Stick or Apple TVTM to play games, stream videos and share photos on the big screen in the comfort of your own home.

Specifications

Display/image Display technology DIP

Resolution 1080p Full HD (1920x1080)

3,600 lumens Brightness Contrast ratio 30,000:1 16:9 Native aspect ratio 4:3. 16:9 Aspect ratio - compatible Keystone correction -

horizontal

Keystone correction vertical

Horizontal scan rate 15.375 ~ 91.147Khz Vertical scan rate 24 ~ 85(120 for 3D)Hz

Uniformity

Screen size 2.03m - 2.54m (80in - 100in)(Diagonal)

Lamp info Light source Lamp Lamp watts 240

Lamp life (hours) 4000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)

Ontical

Throw ratio 0.25:1 Projection distance (m) 0.45m - 0.56m Zoom type Fixed 3.72 Focal length (mm) Native offset 118%

Connectivity Connections

Inputs 1 x HDMI 1.4a 3D support + MHL, 1 x HDMI 1.4a

3D support, 1 x VGA (YPbPr/RGB), 1 x Composite video, 1 x Audio 3.5mm, 2 x USB-A reader/wireless Outputs 1 x VGA, 1 x Audio 3.5mm

Control 1 x RS232, 1 x RJ45

General

3D compatibility

Operating conditions

Noise level (typical) 26dB

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, $\,$

4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p. 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack:

1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D

3D

Security bar, Kensington Lock, Password protected interface Security OSD / display languages

25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish,

Chinese (traditional), Turkish, Vietnamese 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Remote control Data remote with laser and mouse function

Speaker count Watts per speaker 16W

In the box AC power cord Remote control 2x AAA batteries Basic user

> Yes Yes

LAN - control LAN - display

Power

Networking

100 ~ 240V, 50 ~ 60Hz Power supply

0.5W Power consumption (standby) 275W

Power consumption (max) Weight and dimensions

Net weight 3.9kg Dimensions (W x D x H) 343 x 383 x 112

(mm)

