

ZU607T

High brightness professional laser projector



- **Bright WUXGA laser projector - 6,500 lumens**
- **30,000 hours maintenance-free laser light source**
- **Control with HDBaseT 3.0, RS232 & OMSL**
- **4K, HDR & HLG Compatibility**

Introducing the ZU607T.

At 6,500 lumens, with 4K and HDR compatibility, the ZU607T features a dust resistant IP6X certified optical engine for 24/7 operational capabilities and low maintenance. The ZU607T projector features an extremely long-life laser technology, manual horizontal & vertical lens shift and built-in 15W speakers.

Suitable for a wide variety of applications, this projector is perfect for anywhere that requires a clean bright image including large venues, classrooms/lecture theatre's, museums, houses of worship, digital signage, simulation and immersive installations.

The added control flexibility of HDBaseT 3.0 and LAN make this projector an affordable set and forget solution

Specifications

EAN: 5055387668515, Colour: White

The following specifications are preliminary and subject to change without notice

Display/image

Display technology	DLP
Resolution	WUXGA (1920x1200)
Brightness	6,500 lumens
ANSI brightness	5,200
Contrast ratio	300,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9,16:10
Keystone correction - horizontal	+/-30°
Keystone correction - vertical	+/-30°
Has vertical auto keystone correction	Yes
Displayable colours (millions)	1073.4
Horizontal scan rate	5k~140kHzKHz
Vertical scan rate	24~120HzHz
Uniformity	85%
Screen size	0.8m ~ 7.67m (31.5" ~ 301.8") diagonal

Lamp info

Light source type	Laser
LASER life	30,000 hours

Optical

Throw ratio	1.2:1 ~ 1.92:1
Projection distance	1.3m - 7.8m / 51.18" - 307.09"
Zoom	1.6
Zoom type	Manual
Focal length	17.63 ~ 27.9
Lens shift	Vertical -100 ~ 120%, Horizontal: +/-10%
Native offset	120%
Lens shift	Yes - {{downloads_link}}

Connectivity

Connections	Inputs 2 x HDMI 2.0, 2 x VGA, 1 x Composite video, 2 x Audio 3.5mm, 1 x USB-A power 1.5A Outputs 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x 3D sync, 1 x 12V trigger Control 1 x HDBaseT 4K, 1 x RJ45, 1 x RS232
-------------	---

LAN - wireless networking

No

General

Noise level (min)	33dB
Noise level (max)	36dB
3D	Full 3D
Security	Security bar, Kensington Lock, Password protected interface
IP rating	IP6X
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
24/7 operation	Yes
360° operation	Yes
Remote control	Backlit ProAV remote
Heat dissipation	883BTU/hour
Speaker count	2
Watts per speaker	15W
In the box	AC power cord Remote control 2x AAA batteries Basic user manual

Networking

LAN - control	Yes
LAN - wireless networking	No
LAN	Yes

Power

Power supply	Universal AC 100--240V± 10%~ 50 / 60 Hz with PFC input
Power consumption (standby)	<0.5W
Power consumption (min)	300W
Power consumption (max)	366W

Weight and dimensions

Dimensions (W x D x H)	374 x 302 x 117 mm / 14.72" x 11.89" x 4.61"
Gross weight	8.6 kg / 18.96 lbs
Net weight	6.3 kg / 13.89 lbs

