



# PA-912S

Order No.: 0177000

## PRODUCTINFOS

### Mono PA power amplifier

- 1 x 120 W
- Temperature-controlled fan, continuously adjustable
- Protected against overheating, overload and short circuit
- LED indication for clip, protect, overtemperature, output level and 100 V/70 V
- Feed-through output (link)
- Speaker outputs via screw terminal contacts

## TECHNICAL SPECIFICATIONS

### PA-912S

Power rating	120 W
Power rating at 100 V	1 x 120 W
Output impedance	70 V/40 $\Omega$ , 100 V/80 $\Omega$
Channels	1
Inputs	670 mV/10 k $\Omega$ , balanced
Frequency range	80-16,000 Hz
S/N ratio	> 98 dBA
THD	< 1%
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	225 VA
Admiss. ambient temp.	0-40 °C

**PA-912S**

Width	483 mm
Height	44 mm
Depth	255 mm
Rack spaces, RS	1
Weight	3.5 kg
Connections	1 x combo 6.3 mm/XLR (input), 1 x XLR (link), screw contacts (speakers)
Packing dimensions (W x H x L)	0.36 x 0.14 x 0.54 m
Gross weight	4.69 kg
Net weight	3.72 kg