
HDMI CAT5 Extender Series

ITEM NO.: HE02 HDMI CAT5 Extender With RS232 & IR over Single CAT5 cable

HE02 HDMI CAT5 Extender is using only one cost effective CAT5E/6 cable to extend your HDTV display up to 100 meters at 1080p. With Bi-directional RS232 and IR function to delivers significant value to the entire home and commercial entertainment system.




HE02 HDMI CAT5 Extender With RS232 & IR over Single CAT5 cable Features:


- Extends HDMI with control signal over one CAT5/5e/6 cables.
- Controls signals including RS232 and IR remote control.
- Uncompressed high definition video up to 1080p@60Hz@48bits and 3D.
- Max. Data Rate- 10.2 Gbps.
- HDMI 1.3 and HDCP compliance.
- Bi-Directional IR function.
- Bi-Directional RS232 interface commands and data can flow in both directions via RS232, allowing status requests and control of the destination unit.
- Audio transmission support Dolby TrueHD, DTS-HD MA.
- Transmission range up to 100 meters at 1080p resolution.

Panel view:


HE02T



HE02R



Installation view:



Cable:

Link cable recommend use high quality Cat.5e \ Cat.6 \ Cat.6a \ Cat.7 UTP / STP or FTP cable.

Transmission Distance:

The maximum transmission distance up to 100meters, use lower resolution won't extend longer distance

If connection through the wall socket, the cable length must less 5 meters between HDMI extender and wall jack, as below drawing:



RJ45 Define:

Video Link (TIA/EIA-568-B)

1. Orange-white	DATAO +
2. Orange	DATAO -
3. Green-white	DATA1 +
4. Blue	DATA2 +
5. Blue-white	DATA2 -
6. Green	DATA1 -
7. Brown-white	DATA3 +
8 Brown	DATA3 -

LED Indication:

GREEN power
BLUE IR Receive
RED IR Transmitt

RJ-45 GREEN Link

Caution:

- 1. The wiring must away from any equipment with electromagnetic wave, i.e.: mobile phone, microwave, radio equipment, fluorescent lamp, high voltage power lines.
- 2. This device is not network equipment, do not connect with Network to avoid damage.
- 3. IR transmitter do not put near from receiver to avoid mutual interference.

Package Include:

Transmitter x 1 piece
Receiver x 1 piece
Power adapter x 2 pieces
IR Emitter cable x 2 pieces
IR Receiver cable x 2 pieces

Specification:

ITEM	HE02T	HE02R
Resolution	Up to 1080p / 60Hz / 48 bit	
Distance	100M (Max)	
HDMI Connector	Type A	
RS-232 Baud Rate	Up to 115200 bps / Full Duplex	
RS-232 Connector	DB9 Female	DB9 Male
IR Carrier	38Khz / ±10° / 5M / 2 Way	
Power Supply	DC 5V 2AMP Regulated	
Power Consumption	600mA (Max)	1200mA (Max)
Temperature	Operation: 0 to 55℃, Storage: -20 TO 85℃, Humidity: up to 95%	
Dimensions	88 x 130 x 30	
Weight	255	270



Rev. B