

XTOUCH

Intuitive Remote Controls



Sleek, glass-to-glass touch controls that make command easy, with simple drag-and-drop programming in Xilica Designer®.

- Xilica offers a wealth of control options for its Solaro and Neutrino Series processors. These run the gamut from our dedicated free iOS and Android XTouchApps to third-party control devices. But Xilica also offers the convenience of our programmable, PoE powered XTouch Series touch controls
- Comprised of the XTouch50 and XTouch80 models, these 5" and 8" touch controls reside on an ethernet network with connected Solaro or Neutrino processors. Program XTouch controls using a one step drag & drop configuration from within the processors Xilica Designer software
- Both models can be mounted in portrait or landscape orientation and are available in black only
- The XTouch50 mounts onto a US/EU/UK 1-gang box or low voltage bracket via the included XTouch50 mounting bracket
- The XTouch80 mounts onto a US 2-gang box or an included 2-gang low voltage bracket via the included XTouch80 mounting bracket. Optional table-top mounting stand available
- Installation guide and template included with each XTouch or download the XTouch installation guide from our web site

Engineer's Specification

XTouch50 will be a 5-inch touch screen remote control with an HD 1280x720 resolution display. It should support multiple pages with password protection and any set of levels, toggles, selectors, presets, and/or commands. Using the Xilica Designer software, users should be able to drag and drop any DSP parameter or preset and resize the controls, layout, and text as desired. The product should be DHCP-enabled and connect to a network with a Cat5/6 RJ45 connector. Power should be sourced from an IEEE 802.3af standard PoE-compliant network switch or locally using a 24VDC external power supply (not included). The product should be wall mountable onto US/EU/UK 1-gang back boxes or low voltage brackets using the included XTouch50 wall-mount bracket. The control shall be compliant with FCC Part 15 emission and RoHS requirements. Warranty shall be 1 year parts and labor. The control shall be the XTouch50.

XTouch80 will be an 8-inch touch screen remote control with an HD 1280x800 resolution display. It should support multiple pages with password protection and any set of levels, toggles, selectors, presets, and/or commands. Using the Xilica Designer software, users should be able to drag and drop any DSP parameter or preset and resize the controls, layout, and text as desired. The product should be DHCP-enabled and connect to a network with a Cat5/6 RJ45 connector. Power should be sourced from an IEEE 802.3af standard PoE-compliant network switch or locally using a 24VDC external power supply (not included). The product should be wall mountable onto US 2-gang back boxes or an included 2-gang low voltage bracket using the included XTouch80 wall-mount bracket. The control shall be compliant with FCC Part 15 emission and RoHS requirements. Warranty shall be 1 year parts and labor. The control shall be the XTouch80.



Left to right: XTouch50, XTouch80 portrait and landscape

Technical Specifications (XTouch50)

Screen size	5" touch screen
Display	HD 1280 x 720 resolution
Color depth	16.7M colors, 400 nits brightness
Connectors	RJ45 Ethernet, External power supply (not included)
Power	Power over Ethernet (PoE) or 24VDC external power supply (not included)
Mounting orientation	Portrait or landscape (user-defined)

Wall mount	Mount onto US/EU/UK 1-gang back box or low voltage bracket using the included XTouch50 wall-mount bracket
Rack mount	Optional 2RU rack mount panel with 1-gang threaded cut out
Dimensions	5.2"x3.2"x1.3" (132x81x34mm)
Weight	0.4lbs / 0.2kg
Warranty	1 year, parts and labor

Technical Specifications (XTouch80)

Screen size	8" touch screen
Display	HD 1280 x 800 resolution
Color depth	16.7M colors, 400 nits brightness
Connectors	RJ45 Ethernet, External power supply (not included)
Power	Power over Ethernet (PoE) or 24VDC external power supply (not included)
Mounting orientation	Portrait or landscape (user-defined)

Wall mount	Mount onto US 2-gang back box or included low voltage bracket using the included XTouch80 mounting bracket
Rack mount	Optional 4RU rack mount panel with 2-gang threaded cut out
Table-top	Optional TM80 table-top mounting stand
Dimensions	8.7"x5.8"x1.5" (223x149x38mm)
Weight	1lbs / 0.5kg
Warranty	1 year, parts and labor

*Specifications subject to change



Customer Support

If you'd like to contact us regarding product support or technical designs, email support@xilica.com and we'll connect you with a solutions engineer. Alternatively, if you'd like to speak to someone, you can call the following numbers for immediate assistance:

International:	+1 905 770-0055
US Toll Free:	+1 877 767-0234
Europe:	+31 29940-1100
China & Hong Kong SAR:	+852 2604-9382

